



YOUNG'S CORPORATION

242-8 YANGJAE-DONG, SEOCHO-GU, SEOUL, 137-132, KOREA

TEL: 82-2-555-1040 FAX: 82-2-2057-0399

E-mail: export@youngscorp.com Website: www.youngscorp.com

ANTI-S

ANTI SAGGING AGENT

Description

ANTI-S is a pre-activated polyamide wax dispersion that improves the rheological properties of non-aqueous systems. It can be widely used for excellent sag & settling resistance without adversely affecting other film properties.

ANTI-S also provides excellent suspension and alignment of metallic, special effect and matting pigments.

Applications

For use in a variety of applications including metallic and special effect coatings, wood and furniture industry finishes, high gloss industrial and maintenance coatings, automotive & OEM(original equipment manufacturing) coatings, sealants and caulks.

Heavy duty coating, High build coating, Industrial coating , Plastic coating,

Advantages

- * Excellent sag resistance
- * Excellent pigment suspension and anti settling
- * Enhanced coating appearance with metallic and effect pigments
- * No adverse effects on film clarity and gloss
- * Easily incorporated pre-activated paste, including post-blend
- * Non-seeding at elevated temperatures
- * Excellent Suspension of Matting Pigment

Specification

Chemical Description	Polyamide dispersed in solvent
Appearance	Light white soft paste
Solid contents	20±1 %
specific gravity	0.89
Solvent	Xylene / alcohol

Use Levels & Incorporation

Pigment Suspension 0.5-2.0%

Sag Resistance 1.0-5.0%

Packing

1FCL : 17 Kg can * 660 Cans = 11,220 Kg