



# YOUNG'S CORPORATION

242-8 YANGJAE-DONG, SEOCHO-GU, SEOUL, 137-132, KOREA

TEL: 82-2-555-1040 FAX: 82-2-2057-0399

E-mail: [export@youngscorp.com](mailto:export@youngscorp.com) Website: [www.youngscorp.com](http://www.youngscorp.com)

## Toluene

### Description

Toluene has high solubility and evaporation rate, being used as solvents for paint, ink, adhesives and most of the coatings. HS Code : 2902-30-0000

### Applications

Paint, Ink

### Specification

Item	Specification	Unit	Test Method
Specific Gravity, 15.56/15.56 °C	0.869~0.873		ASTM D4052
Sulfur Compounds	None Detected		ASTM D853
Copper Corrosion	Pass		ASTM D849
Acidity	None Detected	Wt-%	ASTM D847
Total Distillation Range at 760 mmHg Pressure -Initial Boiling Point -Dry Point	Not more than 1 °C including the temperature of 110.6°C	°C	ASTM D850
Color (Pt-Co Scale)	Max. 20		ASTM D1209
Acid Wash Color	Max. 2		ASTM D848
Non-Aromatics	Max. 1.4	Vol-%	UOP 744

### Packing :

174Kg / drum \* 80 drums = 13.92 MT